

MAIN COMMUNITY ROUTE BEHAVIOURAL SIGN

NOTES

- 1 THIS DRAWING IS TO BE READ IN CONJUNCTION WITH MIS05 CLAUSE 4.10.
- 2 SIGN LEGENDS, BORDERS AND LOGOS ARE TO BE AS DETAILED ON THIS DRAWING. WHERE A BLUE COLOUR IS SPECIFIED THE COLOUR SHALL BE AS2700 B23 (BRIGHT BLUE). BACKGROUNDS ARE TO BE REFLECTIVE CLASS 1. BORDERS ARE TO BE 6mm WIDE WITH 8mm GAP TO EDGE OF BLADE.
- 3 FOR EXAMPLES OF SIGNAGE LAYOUTS REFER TO ACTSD-0590 TO 0595
- 4 WHERE POSSIBLE SIGNS ARE TO BE MOUNTED ON A SINGLE POST. REFER TO ACTSD-3630 FOR POST AND FOOTING DETAIL.
- 5 GC-50 SIGNS ARE TO BE INSTALLED IN PAIRS AT GENERALLY 500m TO 1km SPACING ON MAIN COMMUNITY ROUTES ONLY. THE SIGN MAY BE INSTALLED ON OTHER PATHS TO ADDRESS REPORTED BEHAVIOURAL ISSUES ON APPROVAL FROM THE ROAD AUTHORITY.
- 6 AT MAIN INFLOW POINTS OF PEOPLE ONTO AN MCR THE SIGN SHOULD BE INSTALLED TO ADDRESS PEOPLE TRAVELLING IN EITHER DIRECTION ON THE MCR. THIS MAY REQUIRE A SPLIT INSTALLATION OF SIGNAGE.
- 7 THE SIGN IS TO BE INSTALLED UTILISING EXISTING POLES SUCH AS LIGHT POLES WHEREVER POSSIBLE. THE SIGN MAY ALSO BE INSTALLED TO SHARE A POLE WITH PAIRED SINGLE SIGN INSTALLATIONS SUCH AS "ROAD AHEAD" SIGNS.

