


- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH MISO5 4.10. ALI SIGN MATERIALS ARE TO BE IN ACCORDANCE WITH MITS14. FOR SIGN BLADE MOUNTING HEIGHTS REFER TO ACTSD-3601
- 2 SIGN LEGENDS (AS1744:2015 SERIES C), BORDERS AND LOGOS ARE TO BE AS DETAILED ON THIS DRAWING AND IN ACCORDANCE WITH THE SIGN LAYOUT GUIDANCE DETAILED ON ACTSD-0574, ADDITIONAL DETAIL FOR PCR SIGNS IS INCLUDED ON ACTSD-0576. BLUE COLOUR LETTERING AND SYMBOLS ARE TO BE AS2700 B23 (BRIGHT BLUE). TOURIST DESTINATIONS SHALL HAVE A WHITE LEGEND ON AS2700 X65 (DARK BROWN) BACKGROUND. WHITE LETTERING SHALL BE CLASS 400 MATERIAL. BORDERS ARE TO BE 6mm WIDE WITH 8mm GAP TO EDGE OF BI ADF
- SIGNS ARE TO BE LOCATED TO BE CONSPICUOUS TO PATH USERS AND MINIMISE RISK OF CONFUSION TO MOTORISTS. SIGNS MUST NOT BE CO-LOCATED WITH ROAD DESTINATION SIGNAGE.
- 4 ARROW DIRECTIONS MAY BE STRAIGHT (S), LEFT (L), RIGHT (R), LEFT OBLIQUE (LOBL) OR RIGHT OBLIQUE (ROBL).
- FOR EXAMPLES OF SIGNAGE LAYOUTS REFER TO ACTSD-0591 TO -0595
- REFER TO ACTSD-3630 FOR POST AND FOOTING DETAIL.
- $(\ 7\)$ for amenity plate designs refer to actsd-0573.
- (8) PCR LABELS AND BRANDS ARE AS SHOWN ON ACTSD-0575
- DESIRABLE MAXIMUM LENGTH OF I SECTION FINGERBOARD IS 0.85m.

 IF A GREATER LENGTH IS REQUIRED THEN PLACE THE DESTINATIONS ON TWO LINES IE: USE GC-42. IF MULTIPLE DESTINATIONS ARE REQUIRED USE MULTIPLE SIGNS, A GC-43 OR SEEK THE APPROVAL OF THE ROAD AUTHORITY FOR A SIGN LENGTH GREATER THEN 0.85m. SIGNS GREATER THAN 0.85m IN LENGTH SHALL BE RAISED ABOVE STANDARD MOUNTING HEIGHT TO REDUCE INCIDENCE OF VANDALISM. MAXIMUM MOUNTING
- REFER TO ACTSD-0574 FOR ADDITIONAL LCR DIRECTIONAL SIGN DESIGN
- A THREE DIRECTION LCR ROUTE SIGN (GC-45) MAY BE USED IN SOME LOCATIONS, REFER TO ACTSD-0592 FOR AN EXAMPLE OF USE AND TO ACTSD-0574 FOR DESIGN AND LAYOUT GUIDANCE



FIRST ISSUE

ACTSD-0572

28/09/1

Date