











RRPM'S AT LARGE TRAFFIC ISLANDS/EXPRESSWAY RAMPS
(ANY SIDE GREATER THAN 12m LONG)

RRPM'S AT SMALL TRAFFIC ISLANDS
(ALL SIDES LESS THAN OR EQUAL TO 12m LONG)

## NOTES

- $\begin{tabular}{llll} \hline & & FOR TRIANGULAR ISLANDS WITH EACH SIDES $\le 5.0m$ ALL KERB LENGTHS TO BE PAINTED WITH WHITE GORE (E6) \\ \hline \end{tabular}$
- 2) PAINT ISLAND NOSE TP TO TP WITH WHITE GORE
- INSTALL YELLOW RRPM'S IN GORE AREA AT 6.0m CENTRES
   (TYPICAL)
- (4) INSTALL WHITE RRPM'S IN GORE AREA AT 6.0m CENTRES (TYPICAL)
- (5) INSTALL YELLOW RRPMS AT 4.0m MINIMUM CENTRES (6.0m CENTRES DESIRABLE, 12.0m MAXIMUM CENTRES)
- 6 INSTALL WHITE RRPMS AT 4.0m MINIMUM CENTRES (6.0m CENTRES DESIRABLE, 12.0m MAXIMUM CENTRES)
- 7) INSTALL RED RRPMS AT 4.0m MINIMUM CENTRES (6.0m CENTRES DESIRABLE, 12.0m MAXIMUM CENTRES)
- B1 (LLM); LLM DENOTES LONG LIFE MATERIAL SUCH AS THERMOPLASTIC, COLD APPLIED PLASTIC AND CEMENT BASED PRODUCTS CAPABLE OF HAVING GLASS BEAD AND NON-SLIP MEDIA APPLIED
- (9) 10m B1 (LLM) SEE NOTE 8
- 10 10m BB (LLM) SEE NOTE 8
- (1) WHITE CHEVRONS ARE TO BE PAINTED BETWEEN ISLAND AND B1 (ONLY IF CLEAR GAP IS GREATER THAN 600mm)
- 3.0m MAX CHEVRON (USE 2 SEPARATE CHEVRONS WHERE GORE GREATER THAN 4m WIDE)
- 13 ALL DIMENSIONS SHOWN ARE IN mm UNLESS SHOWN
  OTHERWISE



## PAVEMENT MARKINGS TRAFFIC ISLANDS

Authorised: Maladal			
Latest Revision Details			
0	BASED ON DRG DS9-04		19-12-18
Rev	Amendment		Date
Drawing No. Revisi		Revisio	on
	ACTOD DEAD		Λ
	ACTSD-3503		U